

Aluminum Self-closing Hinge

Interior door/Lightweight door/Aluminum door


W41K/W41M




Looking for hinge replacement?
Waterson Self-closing Hinge makes your door as good as new!

Hinge models									
Model	Full Name	Door Thickness	Mortise width on door F1 (min.)	Mortise width on frame F2 (min.)	Mortise depth E (min.)	Gap btw. Door and frame when closed			
W41K	Self-closing- Aluminum Flush hinge- Non mortise	40~50 mm Retrofit	Non mortise	Non mortise	Non mortise	3.5~5 mm			
	Self-closing- Aluminum Flush hinge- Mortise on frame	40~50 mm	Non mortise	38.5 mm	3.5~5 mm	< 1.5 mm			
W41M~435 4*3.5" (H*W)	Self-closing- Aluminum Mortise hinge-4*3.5"	30~40 mm	26.5 mm	26.5 mm					
W41M~400 4*4" (H*W)	Self-closing- Aluminum Mortise hinge-4*4"	40~45 mm	33.5 mm	33.5 mm	3.3 mm	1.2~1.9 mm			
W41M~450 4.5*4.5" (H*W)	Self-closing- Aluminum Mortise hinge-4.5*4.5"	45~50 mm	38.5 mm	38.5 mm					

^{**} For non-mortise installation, preserve at least 8.5 mm gap between door and frame.





Models for Waterson Aluminum Self-closing hinge

Тор	Function	Bottom	Function	Type for order	Mechanism
Н	Hydraulic Buffer	S	Spring power (provide door closing power)	HS	Hydraulic Buffer + Spring power
S	Spring power (provide door closing power)	Α	Control closing speed in 20°-90°	SA	Spring power + Mechanical buffer
S	Spring power (provide door closing power)	В	Hold-open in 90°±5°	SB	Spring power + Hold-open

Hinge combination and positions

HS (Hydraulic buffer +Spring)

Hold open at 85°+/-5°

For interior door \leq 70kg Door height \leq 2150 mm Door width \leq 1050 mm

SB (Spring +Hold open)

HS (Hydraulic buffer +Spring)

Self-closing without hold open

For interior door \leq 70kg Door height \leq 2150 mm Door width \leq 1050 mm

SA (Spring + Mechanical buffer)



